

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

SU 001751121 A1
JUL 1992


★SUGB Q35 93-256294/32 ★SU 1751121-A1
Feeding filter sludge into pipeline - air pressures in bunker and
aerating chamber are equalised

SUGAR IND RES INST 90.03.19 90SU-4804200

(92.07.30) B65G 53/48

The sludge is homogenised in the bunker (2) by the paddle mixer (3) and is fed uniformly to the screw pump (1) by admitting compressed air into the bunker. The screw pump discharges the sludge into the aeration chamber (7) for conveying through the pipeline (5). The pressures in the bunker and aeration chamber are equalised to prevent loss of air through the screw pump.

USE/ADVANTAGE - To increase the throughput of concentrated sludges produced in sugar factories. Bul. 28/30.7.92 (2pp)
Dwg.No.1/1)
N93-197112



© 1993 DERWENT PUBLICATIONS LTD.

Derwent House, 14 Great Queen Street, London WC2B 5DF England, UK
US Office: Derwent Inc., 1313 Dolley Madison Blvd., Suite 401, McLean VA 22101, USA

Unauthorised copying of this abstract not permitted